

The manufacturer declares hereby, that all power supplies listed below, are in conformity with the provisions of the following European Directives:

89/336 and 93/68/EEC Electromagnetic Compatibility Directive
73/23 and 93/68 /EEC Low Voltage Directive

XT40.241	Input: 3AC 400V	Output: DC 24V ; 40A
XT40.242	Input: 3AC 480V	Output: DC 24V ; 40A
XT40.361	Input: 3AC 400V	Output: DC 36V ; 26.6A
XT40.362	Input: 3AC 480V	Output: DC 36V ; 26.6A
XT40.481	Input: 3AC 400V	Output: DC 48V ; 20A
XT40.482	Input: 3AC 480V	Output: DC 48V ; 20A
XT40.721	Input: 3AC 400V	Output: DC 72V ; 13.3A
XT40.722	Input: 3AC 480V	Output: DC 72V ; 13.3A

The following standards were used to assess the products:

EN 61000-6-4:2001 **Generic Emission Standard**

- EN 55011 class B and EN 55022 class B for line-routed emissions
- EN 55011 class A and EN 55022 class A for radiated emissions
Configuration: Power supply on table, resistance load,
line length load/mains line: 1m for line-routed emissions (150kHz-30MHz)
line length load/mains line: 1m horizontal and 0,8m vertical for radiated emissions (30MHz-1GHz)
- Meets the requirements of **EN 61000-3-2** Harmonics
- Meets the requirements of **EN 61000-3-3** Voltage changes, voltage fluctuations and flicker

EN 61000-6-2:2001 **Generic Immunity Standard**

(also meets the requirements of EN 61000-6-1:2001)

- EN 61000-4-2 (IEC 61000-4-2) Electrostatic discharge
- EN 61000-4-3 (IEC 61000-4-3) Radio frequency electromagnetic field. Amplitude modulated.
- EN 61000-4-4 (IEC 61000-4-4) Fast Transients
- EN 61000-4-5 (IEC 61000-4-5) Surges
- EN 61000-4-6 (IEC 61000-4-6) Radio frequency common mode. Amplitude modulated.
- EN 61000-4-11 (IEC 61000-4-11) Voltage dips and interruptions

EN 60950-1:2001 **Information technology equipment - Safety - Part 1: General requirements**

PULS as the manufacturer is liable for this declaration.

PULS Elektronische Stromversorgungen GmbH
Arabellastraße 15
D- 81925 München

Munich, 04.10.2006

Bernhard Erdl , Managing Director

No. G 353 1